

## Available Sizes

8.5'x14'TA 8.5'x16'TA 8.5'x18'TA 8.5'x20'TA

## Structure

Aluminum tube frame (floor, walls, & ceiling)  
 16" o/c floor, walls & roof supports  
 Integrated main frame  
 24" V-nose  
 2 5/16" coupler  
 2000# tongue jack  
 Smooth aluminum fenders

## Axles

Dexter torsion ride 3500#

## Tire / Wheels

Silver mod wheels with radial tires

## Doors

32"x74" Side entry door with flush lock  
 Rear ramp door with spring assist

## Electrical

Clear LED marker & break lights  
 2 Interior dome light with wall switch  
 Interior mounted battery & junction box  
 7 way round plug

## Exterior

Screwless .030 bonded aluminum skin  
 Screwless 3" upper rub rail  
 Seamless one-piece aluminum roof (triple sealed)  
 24' ATP Stoneguard  
 2 side wall vents  
 Aluminum grab handles  
 48" Aluminum bar locks with grease fitting (ramp door)  
 Aluminum door hinges

## Interior

3/4" Water resistant flooring  
 3/8" Water resistant walls  
 ATP Interior cove trim



Trailer Model	DBET 8.5x14 TA	DBET 8.5x16 TA	DBET 8.5x18 TA	DBET 8.5x20 TA
OVERALL LxWxH	102"x224"x98"	102"x248"x98"	102"x272"x98"	102"x296"x98"
BOX LxWxH	99.5"x168"x86.5"	99.5"x168"x86.5"	99.5"x168"x86.5"	99.5"x168"x86.5"
INTERIOR LxWxH	96"x166"x78.25"	96"x190"x78.25"	96"x214"x78.25"	96"x238"x78.25"
V-NOSE	30"	30"	30"	30"
PLATFORM HEIGHT	17.75"	17.75"	17.75"	17.75"
REAR DOOR WXH	91" x 76.25"	91" x 76.25"	91" x 76.25"	91" x 76.25"
HITCH HEIGHT	16.75" top of ball	16.75" top of ball	16.75" top of ball	16.75" top of ball
HITCH BALL SIZE	2 5/16"	2 5/16"	2 5/16"	2 5/16"
HITCH RATING	11000#	11000#	11000#	11000#
GVWR	7000#	7000#	7000#	7000#
CURB WEIGHT	1950#	2120#	2210#	2350#
PAYLOAD	5050#	4880#	4790#	4650#
AXLE TYPE	Torsion	Torsion	Torsion	Torsion
AXLE RATING	3500#	3500#	3500#	3500#
AXLE QUANTITY	2	2	2	2
TIRES	205/75R15	205/75R15	205/75R15	205/75R15
WHEELS	Silver Mod	Silver Mod	Silver Mod	Silver Mod